

MORE FROM LESS



**ADVANCED
FIREFIGHTING
TECHNOLOGY**



AFT TROLLEY 50/02

- ▶ LOW PRESSURE
- ▶ WATER MIST/CAFS
- ▶ HIGH EFFICIENCY
- ▶ RIDABLE & MOBILE

www.aftwatermist.com

| TECHNICAL SPECIFICATIONS | TROLLEY 50/02 |
|---|--|
| Extinguishing agent tank | |
| Filling capacity as per EN 1866 | 50 litres |
| Material | Stainless steel |
| Working pressure | |
| Pressure at pressure reducer | 8,5 bar |
| Propellant gas bottle | |
| Medium | Compressed air |
| Technical specifications of pressure cylinder | <ul style="list-style-type: none"> • Filling pressure: 300 bar • Volume: 6 litres • Valve connection: G5/8 interior |
| Technical Parameters | |
| Operating time | Approx. 125 sec. |
| Flow rate | 24 litres/min |
| Operating temperature | Tmin + 5°C; Tmax + 60°C |
| Trolley Frame | Double powder coated steel frame |
| Extinguishing gun | |
| Changeover time | Approx. 2 sec. from jet to spray mode |
| Lancing distance | Approx. 16 - 18 m jet mode Approx. 6 - 7 m spray mode |
| Electrical Fires | Up to 1000 V / 3 m distance |
| Hose lengths | 5 m, 10 m, 15 m |
| Ratings (using Ecodare 423) | |
| Fire Class A and B | IVB (as per EN 1866) |
| Dimensions | |
| Weight empty (without air bottle) | Approx. 52 kg |
| Dimensions (LxWxH) | Approx. 620 x 540 x 1110 mm |
| Certifications | |
| Standards | DIN EN 1866, GS, SOLAS, TÜV, ISO 9001 (manufacturer)* |

* Country and sector-specific regulations have higher priority. If you have any questions, please contact AFT GmbH.



- "MADE IN GERMANY"
- JET AND SPRAY MODE
- EASY TO OPERATE
- SUITABLE FOR MANY EXTINGUISHING AGENTS
- CONSISTENT WATER MIST SPRAY
- V4A STAINLESS STEEL CONTAINER
- EASY TO MOVE
- EASY TO FILL
- LOW WORKING PRESSURE
- CERTIFICATION IN ACCORDANCE WITH EN 1866